


涼厨® ガス回転釜

製品	型式	容量(ℓ)	内釜材質			製品寸法 間口×奥行×高さ*2(mm)	13Aガス消費量		LPガス消費量		ガス 接続口	電源	消費電力 (kW)	給水 給湯	価格(税抜)						
			ステンレス	アルミ	鋳鉄		(kW)	(kcal/h)	(kW)	(kg/h)					内釜:ステンレス	内釜:アルミ	内釜:鋳鉄				
高効率ケトル	HTK-140	140* ^{※1}	○	—	—	1518× 980×1880	19.0	16,300	19.0	1.36	15A	单相 100V	0.04	—	¥2,398,000	—	—				
スーパーガスケトル	OH-110 FC-LS	鋳 鉄: 107*	○	—	○	鋳 鉄:1505× 956×1820	30.2	26,000	30.2	2.17	15A	—	—	15A	—	—	¥2,349,000				
	OH-110 SUS-LS	ステンレス: 109*				ステンレス:1503× 956×1850									¥2,524,000						
	OH-140 FC-LS	鋳 鉄: 139*				鋳 鉄:1544×1004×1940									—			¥2,503,000			
	OH-140 SUS-LS	ステンレス: 130*				ステンレス:1565×1004×1940									¥2,730,000						
	OH-180 FC-LS	鋳 鉄: 178*				鋳 鉄:1755×1115×2050									—			¥2,761,000			
	OH-180 SUS-LS	ステンレス: 192*				ステンレス:1769×1115×2120									¥3,039,000						
スーパーガスケトル	OH-110	鋳 鉄: 107*	○	—	○	鋳 鉄:1505× 956×1820	30.2	26,000	30.2	2.17	15A	—	—	15A	¥2,493,000	—	¥2,318,000				
		ステンレス: 109*				ステンレス:1503× 956×1850															
	OH-140	鋳 鉄: 139*				鋳 鉄:1544×1004×1940									34.9		30,000	34.9	2.50	¥2,699,000	¥2,472,000
		ステンレス: 130*				ステンレス:1565×1004×1940															
	OH-180	鋳 鉄: 178*				鋳 鉄:1755×1115×2050									46.5		40,000	46.5	3.33	¥3,008,000	¥2,730,000
		ステンレス: 192*				ステンレス:1769×1115×2120															
スーパーガスケトルII	OH2-110 FC-LS	鋳 鉄: 107*	○	—	○	鋳 鉄:1480× 936×1750	30.2	26,000	30.2	2.17	15A	—	—	—	お問い合わせ	お問い合わせ	お問い合わせ				
	OH2-110 SUS-LS	ステンレス: 109*				ステンレス:1480× 936×1750															
	OH2-140 FC-LS	鋳 鉄: 139*				鋳 鉄:1590×1004×1870												34.9	30,000	34.9	2.50
	OH2-140 SUS-LS	ステンレス: 130*				ステンレス:1560×1004×1900												46.5	40,000	46.5	3.33
	OH2-180 FC-LS	鋳 鉄: 178*				鋳 鉄:1738×1115×2060															
	OH2-180 SUS-LS	ステンレス: 192*				ステンレス:1770×1115×2100															
スーパーガスケトルII	OH2-110	鋳 鉄: 107*	○	—	○	鋳 鉄:1480× 936×1760	30.2	26,000	30.2	2.17	15A	—	—	—	お問い合わせ	お問い合わせ	お問い合わせ				
		ステンレス: 109*				ステンレス:1480× 936×1760															
	OH2-140	鋳 鉄: 139*				鋳 鉄:1590×1004×1870												34.9	30,000	34.9	2.50
		ステンレス: 130*				ステンレス:1560×1004×1900												46.5	40,000	46.5	3.33
	OH2-180	鋳 鉄: 178*				鋳 鉄:1738×1115×2060															
		ステンレス: 192*				ステンレス:1770×1115×2100															
ステンレス製 ガス回転釜 低輻射型	GHSX-26	55	○	○	○	1469× 957×1780	23.3	20,000	23.3	1.67	15A	—	—	—	¥1,281,000	¥1,204,000	¥1,197,000				
	GHSX-28	80				1516×1000×1820	30.2	26,000	30.2	2.17					¥1,302,000	¥1,225,000	¥1,218,000				
	GHSX-30	110				1583×1048×1870	34.9	30,000	34.9	2.50					¥1,323,000	¥1,246,000	¥1,239,000				
	GHSX-32	140				1637×1076×1910	46.5	40,000	46.5	3.33					¥1,449,000	¥1,372,000	¥1,365,000				
	GHSX-35* ^{※3}	190				1769×1158×2110	46.5	40,000	46.5	3.33					¥1,638,000	¥1,582,000	¥1,575,000				
ガスフライ釜	HF-110	107*	—	—	○	1525× 956×1820	30.2	26,000	30.2	2.17	15A	单相 100V	0.04	15A	—	—	お問い合わせ				
	HF-140	140*				1568×1004×1940	34.9	30,000	34.9	2.50											
	HF-180	178*				1775×1115×2050	46.5	40,000	46.5	3.33											
ガスフライ釜	HF2-110	107*	—	—	○	1546× 936×1765	30.2	26,000	30.2	2.17	15A	单相 100V	0.04	15A	—	—	お問い合わせ				
	HF2-140	139*				1656×1004×1870	34.9	30,000	34.9	2.50											
	HF2-180	178*				1785×1115×2060	46.5	40,000	46.5	3.33											
ガスープ マスター	GZT-50LW2	50	○	—	—	1183× 833×1136	18.0	15,500	18.0	1.29	20A	—	—	—	¥1,817,000	—	—				
	GZT-75LW2	75				1183× 833×1084	18.0	15,500	18.0	1.29					¥1,880,000						
	GZT-100LW2	100				1281× 882×1106	23.0	19,800	23.0	1.65					¥2,090,000						

※1 ★印:容量=満水量です。 ※2 高さ:蓋を全開にした時の高さです。 ※3 涼厨®仕様ですが作業環境向上ガス機器の認証品ではございません。

※商標「涼厨」は、大阪瓦敷(株)の登録商標です。

▶ガス回転釜

製品	型式	容量(ℓ)	内釜材質			製品寸法 間口×奥行×高さ*2(mm)	13Aガス消費量		LPガス消費量		ガス 接続口	電源	消費電力 (kW)	給水 給湯	価格(税抜)		
			ステンス	アルミ	鋳鉄		(kW)	(kcal/h)	(kW)	(kg/h)					内釜:ステンレス	内釜:アルミ	内釜:鋳鉄
ステンレス製ガス回転釜 	*1 GHSL4-23	36	○	○	○	1200× 854×1525	23.3	20,000	23.3	1.67	20A	—	—	—	¥491,000	¥435,000	¥428,000
	GHSL4-26	55				1316× 927×1645	23.3	20,000	23.3	1.67					¥500,000	¥443,000	¥436,000
	GHSL4-28	80				1348× 984×1700	37.2	32,000	37.2	2.67					¥511,000	¥454,000	¥447,000
	GHSL4-30	110				1426×1061×1765	37.2	32,000	37.2	2.67					¥553,000	¥491,000	¥484,000
	GHSL4-32	140				1448×1061×1835	50.0	43,000	50.0	3.58					¥581,000	¥549,000	¥542,000
	GHSL4-35	190				1566×1180×2015	50.0	43,000	50.0	3.58					¥778,000	¥729,000	¥722,000
ステンレス製ガス回転釜 	GHS-23	36	○	○	○	1200× 826×1530	23.3	20,000	23.3	1.67	20A	—	—	—	¥399,000	¥333,000	¥326,000
	GHS-26	55				1316× 906×1645	23.3	20,000	23.3	1.67					¥409,000	¥343,000	¥336,000
	GHS-28	80				1348× 946×1700	37.2	32,000	37.2	2.67					¥422,000	¥354,000	¥347,000
	GHS-30	110				1426×1020×1765	37.2	32,000	37.2	2.67					¥470,000	¥398,000	¥391,000
	GHS-32	140				1448×1036×1830	50.0	43,000	50.0	3.58					¥493,000	¥455,000	¥448,000
	GHS-35	190				1566×1158×2015	50.0	43,000	50.0	3.58					¥710,000	¥653,000	¥646,000
間接加熱 ケトル 	JK-40	40	○	—	—	1217× 826×1575	23.7	20,350	23.7	1.70	20A	—	—	—	¥1,089,000	—	—
	JK-60	60				1321× 920×1675	28.0	24,050	28.0	2.01					¥1,177,000		
	JK-100	100				1344× 950×1720	34.4	29,600	34.4	2.47					¥1,243,000		
ガス回転釜 ドライシステムユニット 	GHSD1-23	36	○	○	○	1208×1426×1665	23.3	20,000	23.3	1.67	20A	—	—	20A	¥1,340,000	¥1,284,000	¥1,277,000
	GHSD1-26	55				1312×1503×1665	23.3	20,000	23.3	1.67					¥1,402,000	¥1,344,000	¥1,337,000
	GHSD1-28	80				1334×1543×1665	37.2	32,000	37.2	2.67					¥1,463,000	¥1,405,000	¥1,398,000
	GHSD1-30	110				1408×1573×1665	37.2	32,000	37.2	2.67					¥1,565,000	¥1,502,000	¥1,495,000
	GHSD1-32	140				1424×1643×1730	50.0	43,000	50.0	3.58					¥1,651,000	¥1,622,000	¥1,615,000
	GHSD1-35	190				1522×1663×1800	50.0	43,000	50.0	3.58					¥1,897,000	¥1,827,000	¥1,820,000

※1 GHSL4:ドライシステムに対応した様々なパッケージをご用意しています。くわしくはP.16へ。

※2 高さ:蓋を全開にした時の高さです。

▶ガス回転釜

製品	型式	容量(ℓ)	内釜材質			製品寸法 間口×奥行×高さ*(mm)	13Aガス消費量		LPガス消費量		ガス 接続口	電源	消費電力 (kW)	給水 給湯	価格(税抜)		
			ステンス	アルミ	鋳鉄		(kW)	(kcal/h)	(kW)	(kg/h)					内釜:ステンレス	内釜:アルミ	内釜:鋳鉄
 鋳鉄製ガス回転釜	GHT-23	36				1202× 759×1500	18.8	16,200	18.8	1.35	20A	—	—	—	¥427,000	¥349,000	¥342,000
	GHT-26	55				1314× 870×1630	31.4	27,000	31.4	2.25					¥493,000	¥409,000	¥402,000
	GHT-28	80	○	○	○	1410× 950×1680	31.4	27,000	31.4	2.25					¥537,000	¥448,000	¥441,000
	GHT-30	110				1487×1000×1765	31.4	27,000	31.4	2.25					¥603,000	¥508,000	¥501,000
	GHT-32	140				1554×1030×1835	41.9	36,000	41.9	3.00					¥688,000	¥585,000	¥578,000
 フライヤー仕様	GHSFE-23	36				1200× 826×1525	18.0	15,500	18.0	1.29	20A	単相 100V	0.02	—	—	—	¥825,000
	GHSFE-26	55				1316× 906×1635	18.0	15,500	18.0	1.29							¥847,000
	GHSFE-28	80			○	1348× 946×1700	30.0	25,800	30.0	2.15							¥865,000
	GHSFE-30	110				1426×1020×1765	30.0	25,800	30.0	2.15							¥893,000
	GHSFE-32	140				1448×1036×1818	43.0	37,000	43.0	3.08							¥915,000
	GHSFE-35	190				1565×1158×2015	43.0	37,000	43.0	3.08							¥920,000
 フライヤー仕様	GHSFE II-23	36				1200× 826×1525	18.0	15,500	18.0	1.29	20A	単相 100V	0.02	—	—	—	¥957,000
	GHSFE II-26	55				1316× 906×1635	18.0	15,500	18.0	1.29							¥979,000
	GHSFE II-28	80			○	1348× 946×1700	30.0	25,800	30.0	2.15							¥997,000
	GHSFE II-30	110				1426×1020×1765	30.0	25,800	30.0	2.15							¥1,025,000
	GHSFE II-32	140				1448×1036×1818	43.0	37,000	43.0	3.08							¥1,047,000
	GHSFE II-35	190				1565×1158×2015	43.0	37,000	43.0	3.08							¥1,053,000

※高さ: 蓋を全開にした時の高さです。

▶ガス固定釜

製品	型式	容量(ℓ)	内釜材質			製品寸法 間口×奥行×高さ(mm)	13Aガス消費量		LPガス消費量		ガス 接続口	電源	消費電力 (kW)	給水 給湯	価格(税抜)		
			ステンス	アルミ	鋳鉄		(kW)	(kcal/h)	(kW)	(kg/h)					内釜:ステンレス	内釜:アルミ	内釜:鋳鉄
 鋳鉄製ガス固定釜	GHF-21	28				700×744×655	18.8	16,200	18.8	1.35	25A	—	—	—	¥301,000	¥195,000	¥188,000
	GHF-23	36				740×768×706	18.8	16,200	18.8	1.35					¥353,000	¥253,000	¥246,000
	GHF-26	55	○	○	○	870×870×861	31.4	27,000	31.4	2.25					¥436,000	¥343,000	¥336,000
	GHF-28	80				950×950×907	31.4	27,000	31.4	2.25					¥475,000	¥390,000	¥383,000
 野外移動煮炊釜	GHRF-23	36				800×825×663			18.8	1.35	10A	—	—	—	¥262,000	¥190,000	
	GHRF-26	55	○	○	—	900×870×723	—	—	31.4	2.25					¥317,000	¥241,000	—
	GHRF-30	110				948×948×895			31.4	2.25					¥476,000	¥392,000	