








涼厨® ガス回転釜

製品	型式	容量(ℓ)	内釜材質			製品寸法 間口×奥行×高さ*2(mm)	13Aガス消費量		LPガス消費量		ガス 接続口	電源	消費電力 (kW)	給水 給湯	価格(税抜)					
			ステンレス	アルミ	铸铁		(kW)	(kcal/h)	(kW)	(kg/h)					内釜:ステンレス	内釜:アルミ	内釜:铸铁			
高効率ケトル 	HTK-140	140*1	○	—	—	1518× 980×1880	19.0	16,300	19.0	1.36	15A	单相 100V	0.04	—	¥2,180,000	—	—			
スーパーガasketル 	OH-110	铸铁: 107*	○	—	○	铸铁: 1505× 956×1820	30.2	26,000	30.2	2.17	15A	—	—	15A	¥2,420,000	—	¥2,250,000			
		ステンレス: 109*				ステンレス: 1503× 956×1850														
	OH-140	铸铁: 139*				铸铁: 1544×1004×1940	34.9	30,000	34.9	2.50					¥2,620,000	—	¥2,400,000			
		ステンレス: 130*				ステンレス: 1565×1004×1940														
	OH-180	铸铁: 178*				铸铁: 1755×1115×2050	46.5	40,000	46.5	3.33					¥2,920,000	—	¥2,650,000			
		ステンレス: 192*				ステンレス: 1769×1115×2120														
スーパーガasketルII 	OH2-110	铸铁: 107*	○	—	○	铸铁: 1480× 936×1765	30.2	26,000	30.2	2.17	15A	—	—	—	お問い合わせ	お問い合わせ	お問い合わせ			
		ステンレス: 109*				ステンレス: 1480× 936×1765														
	OH2-140	铸铁: 139*				铸铁: 1590×1004×1870	34.9	30,000	34.9	2.50								お問い合わせ	お問い合わせ	お問い合わせ
		ステンレス: 130*				ステンレス: 1560×1004×1900														
	OH2-180	铸铁: 178*				铸铁: 1738×1115×2060	46.5	40,000	46.5	3.33								お問い合わせ	お問い合わせ	お問い合わせ
		ステンレス: 192*				ステンレス: 1770×1115×2100														
ステンレス製 ガス回転釜 低輻射型 	GHSX-26	55	○	○	○	1469× 957×1780	23.3	20,000	23.3	1.67	15A	—	—	—	¥1,220,000	¥1,140,000	¥1,140,000			
	GHSX-28	80				1516×1000×1820	30.2	26,000	30.2	2.17					¥1,240,000	¥1,160,000	¥1,160,000			
	GHSX-30	110				1583×1048×1870	34.9	30,000	34.9	2.50					¥1,260,000	¥1,180,000	¥1,180,000			
	GHSX-32	140				1637×1076×1910	46.5	40,000	46.5	3.33					¥1,380,000	¥1,300,000	¥1,300,000			
	GHSX-35*3	190				1769×1158×2110	46.5	40,000	46.5	3.33					¥1,560,000	¥1,500,000	¥1,500,000			
ガスフライ釜 	HF-110	107*	—	—	○	1525× 956×1820	30.2	26,000	30.2	2.17	15A	单相 100V	0.04	15A	—	—	お問い合わせ			
	HF-140	140*				1568×1004×1940	34.9	30,000	34.9	2.50										
	HF-180	178*				1775×1115×2050	46.5	40,000	46.5	3.33										
ガスフライ釜 	HF2-110	107*	—	—	○	1546× 936×1765	30.2	26,000	30.2	2.17	15A	单相 100V	0.04	15A	—	—	お問い合わせ			
	HF2-140	139*				1656×1004×1870	34.9	30,000	34.9	2.50										
	HF2-180	178*				1785×1115×2060	46.5	40,000	46.5	3.33										
ガスープ マスター 	GZT-50LW2	50	○	—	—	1183× 833×1136	18.0	15,500	18.0	1.29	20A	—	—	—	¥1,730,000	—	—			
	GZT-75LW2	75				1183× 833×1084	18.0	15,500	18.0	1.29					¥1,790,000					
	GZT-100LW2	100				1281× 882×1106	23.0	19,800	23.0	1.65					¥1,990,000					

*1 ★印: 容量=満水量です。 *2 高さ: 蓋を全開にした時の高さです。 *3 涼厨®仕様ですが作業環境向上ガス機器の認証品ではございません。

※商標「涼厨」は、大阪瓦敷(株)の登録商標です。

▶ガス回転釜

製品	型式	容量(ℓ)	内釜材質			製品寸法 間口×奥行×高さ*2(mm)	13Aガス消費量		LPガス消費量		ガス 接続口	電源	消費電力 (kW)	給水 給湯	価格(税抜)		
			ステンス	アルミ	鋳鉄		(kW)	(kcal/h)	(kW)	(kg/h)					内釜:ステンレス	内釜:アルミ	内釜:鋳鉄
ステンレス製ガス回転釜 	*1 GHSL4-23	36	○	○	○	1200× 854×1525	23.3	20,000	23.3	1.67	20A	—	—	—	¥491,000	¥435,000	¥428,000
	GHSL4-26	55				1316× 927×1645	23.3	20,000	23.3	1.67					¥500,000	¥443,000	¥436,000
	GHSL4-28	80				1348× 984×1700	37.2	32,000	37.2	2.67					¥511,000	¥454,000	¥447,000
	GHSL4-30	110				1426×1061×1765	37.2	32,000	37.2	2.67					¥553,000	¥491,000	¥484,000
	GHSL4-32	140				1448×1061×1835	50.0	43,000	50.0	3.58					¥581,000	¥549,000	¥542,000
	GHSL4-35	190				1566×1180×2015	50.0	43,000	50.0	3.58					¥778,000	¥729,000	¥722,000
ステンレス製ガス回転釜 	GHS-23	36	○	○	○	1200× 826×1530	23.3	20,000	23.3	1.67	20A	—	—	—	¥362,000	¥296,000	¥296,000
	GHS-26	55				1316× 906×1645	23.3	20,000	23.3	1.67					¥371,000	¥305,000	¥305,000
	GHS-28	80				1348× 946×1700	37.2	32,000	37.2	2.67					¥383,000	¥315,000	¥315,000
	GHS-30	110				1426×1020×1765	37.2	32,000	37.2	2.67					¥427,000	¥355,000	¥355,000
	GHS-32	140				1448×1036×1830	50.0	43,000	50.0	3.58					¥448,000	¥407,000	¥407,000
	GHS-35	190				1566×1158×2015	50.0	43,000	50.0	3.58					¥645,000	¥587,000	¥587,000
間接加熱 ケトル 	JK-40	40	○	—	—	1217× 826×1575	23.7	20,350	23.7	1.70	20A	—	—	—	¥990,000	—	—
	JK-60	60				1321× 920×1675	28.0	24,050	28.0	2.01					¥1,070,000		
	JK-100	100				1344× 950×1720	34.4	29,600	34.4	2.47					¥1,130,000		
ガス回転釜 ドライシステムユニット 	GHSD1-23	36	○	○	○	1208×1426×1665	23.3	20,000	23.3	1.67	20A	—	—	20A	¥1,276,000	¥1,216,000	¥1,216,000
	GHSD1-26	55				1312×1503×1665	23.3	20,000	23.3	1.67					¥1,335,000	¥1,273,000	¥1,273,000
	GHSD1-28	80				1334×1543×1665	37.2	32,000	37.2	2.67					¥1,393,000	¥1,331,000	¥1,331,000
	GHSD1-30	110				1408×1573×1665	37.2	32,000	37.2	2.67					¥1,490,000	¥1,423,000	¥1,423,000
	GHSD1-32	140				1424×1643×1730	50.0	43,000	50.0	3.58					¥1,572,000	¥1,538,000	¥1,538,000
	GHSD1-35	190				1522×1663×1800	50.0	43,000	50.0	3.58					¥1,806,000	¥1,733,000	¥1,733,000

※1 GHSL4:ドライシステムに対応した様々なパッケージをご用意しています。くわしくはP.16へ。

※2 高さ:蓋を全開にした時の高さです。

▶ ガス回転釜

製品	型式	容量(ℓ)	内釜材質			製品寸法 間口×奥行×高さ*(mm)	13Aガス消費量		LPガス消費量		ガス 接続口	電源	消費電力 (kW)	給水 給湯	価格(税抜)		
			ステンス	アルミ	鋳鉄		(kW)	(kcal/h)	(kW)	(kg/h)					内釜:ステンレス	内釜:アルミ	内釜:鋳鉄
 鋳鉄製ガス回転釜	GHT-23	36				1202× 759×1500	18.8	16,200	18.8	1.35	20A	—	—	—	¥395,000	¥316,000	¥316,000
	GHT-26	55				1314× 870×1630	31.4	27,000	31.4	2.25					¥456,000	¥372,000	¥372,000
	GHT-28	80	○	○	○	1410× 950×1680	31.4	27,000	31.4	2.25					¥497,000	¥408,000	¥408,000
	GHT-30	110				1487×1000×1765	31.4	27,000	31.4	2.25					¥558,000	¥463,000	¥463,000
	GHT-32	140				1554×1030×1835	41.9	36,000	41.9	3.00					¥637,000	¥535,000	¥535,000
 フライヤー仕様	GHSFE-23	36				1200× 826×1525	18.0	15,500	18.0	1.29	20A	単相 100V	0.02	—	—	—	¥785,000
	GHSFE-26	55				1316× 906×1635	18.0	15,500	18.0	1.29							¥806,000
	GHSFE-28	80			○	1348× 946×1700	30.0	25,800	30.0	2.15							¥823,000
	GHSFE-30	110				1426×1020×1765	30.0	25,800	30.0	2.15							¥850,000
	GHSFE-32	140				1448×1036×1818	43.0	37,000	43.0	3.08							¥871,000
	GHSFE-35	190				1565×1158×2015	43.0	37,000	43.0	3.08							¥876,000
 フライヤー仕様	GHSFE II-23	36				1200× 826×1525	18.0	15,500	18.0	1.29	20A	単相 100V	0.02	—	—	—	¥911,000
	GHSFE II-26	55				1316× 906×1635	18.0	15,500	18.0	1.29							¥932,000
	GHSFE II-28	80			○	1348× 946×1700	30.0	25,800	30.0	2.15							¥949,000
	GHSFE II-30	110				1426×1020×1765	30.0	25,800	30.0	2.15							¥976,000
	GHSFE II-32	140				1448×1036×1818	43.0	37,000	43.0	3.08							¥997,000
	GHSFE II-35	190				1565×1158×2015	43.0	37,000	43.0	3.08							¥1,002,000

※高さ: 蓋を全開にした時の高さです。

▶ ガス固定釜

製品	型式	容量(ℓ)	内釜材質			製品寸法 間口×奥行×高さ(mm)	13Aガス消費量		LPガス消費量		ガス 接続口	電源	消費電力 (kW)	給水 給湯	価格(税抜)		
			ステンス	アルミ	鋳鉄		(kW)	(kcal/h)	(kW)	(kg/h)					内釜:ステンレス	内釜:アルミ	内釜:鋳鉄
 鋳鉄製ガス固定釜	GHF-21	28				700×744×655	18.8	16,200	18.8	1.35	25A	—	—	—	¥268,000	¥169,000	¥169,000
	GHF-23	36				740×768×706	18.8	16,200	18.8	1.35					¥315,000	¥220,000	¥220,000
	GHF-26	55	○	○	○	870×870×861	31.4	27,000	31.4	2.25					¥389,000	¥298,000	¥298,000
	GHF-28	80				950×950×907	31.4	27,000	31.4	2.25					¥424,000	¥339,000	¥339,000
 野外移動煮炊釜	GHRF-23	36				800×825×663			18.8	1.35	10A	—	—	—	¥238,000	¥169,000	
	GHRF-26	55	○	○	—	900×870×723	—	—	31.4	2.25					¥288,000	¥215,000	—
	GHRF-30	110				948×948×895			31.4	2.25					¥432,000	¥350,000	